

Technical Features

F-LINE 8X2-6X4 Road Series



Technical Features August 2025

Technical Features	3233S	3245S	3545		
Engine	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	
Туре	GEN1.5 Ecotorq Euro 6 115 mm x 144 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	
Displacement (cc)	8.974 cm3	12.740 cm3	12.740 cm3	12.740 cm3	
Power PS (kW)	330 PS (243 kW) @ 1900 d/d	450 PS (330 kW) @ 1800 d/d	450 PS (330 kW) @ 1800 d/d	450 PS (330 kW) @ 1800 d/d	
Torque	1400 Nm @ 1200-1650 d/d	2300 Nm @ 900-1300 d/d	2300 Nm @ 900-1300 d/d	2300 Nm @ 900-1300 d/d	
Powertrain					
Clutch	430 mm Single Disc				
Transmission / Ratios	Automated: ZF AS 1510 TO (9,48 - 0,75) Manual: Eaton 9S 14409 (9,40 - 0,75)	Automated: Ecotorq 16S 2600 DD (17,03 - 1,00)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	4,107 Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	
Forward and Reverse Gear	Automated: 9 forward + 1 reverse Manual: 9 forward + 1 reverse	Automated: 16 forward + 2 reverse	Automated: 16 forward + 2 reverse	Automated: 16 forward + 2 reverse	
FDR	4,63	2,64	4,08	4,08	
Axle & Suspension					
Axle Configuration	8x2	8x2	6x4	6x4	
Front Axle	7,5 T	7,5 T	8 T	8 T	
Rear Axle	XSS-510, 13.5 T	XSS-510, 13.5 T	XPT-330, 16 T	XPT-330, 16 T	
Suspension	Parabolic Front Leaf Spring / Compensating Mechanical Rear Suspension	Parabolic Front Leaf Spring / Compensating Mechanical Rear Suspension	Parabolic Front Leaf Spring / Mechanical Rear Suspension	Parabolic Front Leaf Spring / Mechanical Rear Suspension	
Brakes					
Brake System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	
Service Brake	Front and Rear Disc Brakes	Front and Rear Disc Brakes	Front and Rear Z-Cam Drum Brake System	Front and Rear Z-Cam Drum Brake System	
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 - Disc Brake	430 x 45 Disc Brake	410 x 200 Z-Cam Drum Brake System	410 x 200 Z-Cam Drum Brake System	
Engine Brake Power	max. 220 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	
Hydraulic Retarder	-	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	-	
Fuel & AdBlue Tank					
Fuel Tank	550 L, Right Hand Side, Aluminum	550 L, Right Hand Side, Aluminum	315 L, Right Hand Side, Steel	315 L, Right Hand Side, Steel	
SCR Tank	78 L	78 L	55 L	55 L	
Chassis					
Thickness and Material	U Profile, High Strength, 7 mm Thickness				
Tires					
Front Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	
Rear Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	
Rims	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	

Standard and Optional Features

August 2025

Standard and Optional Features	3233S	3245S	3545		
Safety & Technology	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	
Pre-Collision Assist	•	•	-	-	
Lane Keeping Alert (LDWS)	•	•	•	•	
Pre-Collision Assist	•	•	-	-	
Electronic Stability Program (ESP)	•	•	•	•	
Driver Alert System	•	•	•	•	
Moving-off Information System (MOIS)	•	•	•	•	
Rear View Camera	•	•	•	•	
Blind Spot Information System (BLIS)	•	•	•	•	
Alcohol Interlock Facilitation	•	•	•	•	
Traffic Sign Recognition	•	•	•	•	
Emergency Stop Signal	•	•	•	•	
Tire Pressure Monitoring System (TPMS)	•	•	•	•	
Auto High Beam Headlamps	0	0	-	-	
Pre-Collision Assist with Pedestrian Detection	0	0	-	-	
Intelligent Adaptive Cruise Control with Stop & Go (iACC)	-	0	-	-	
Electronic Brake System with ABS & ATC (EBS)	•	•	•	•	
Electro-Hydraulic Streeing System (EHPAS)	_		0	0	
Retarder	_	0	0	-	
Diferential Lock	•	•	•	•	
Interior	-	-	-		
Multimedia System with 9" Touch Screen (DAB Radio, Bluetooth, USB (A Type - C Type), Apple					
CarPlay, Android Auto, Remote Control)	•	•	•	•	
Navigation	0	0	0	0	
Improved Sound and Heat Insulation	•	•	•	•	
Air Conditioning	•	•	•	•	
Dry & Wet Type Cab Heater	0	0	-	-	
Dry Type Cab Heater	•	•	-	-	
Wet Type Cab Heater	0	0	0	0	
Dual Passenger Seat	-	-	0	-	
Driver Seat Armrest Mattress Topper for Lower Bed	•	•	0	•	
Adjustable Steering Wheel	•	•	•	•	
Driver Seatbelt Warning System	•	•	•	•	
Double Bed and Upper Storage Area	0	0	-	-	
Single Bed (Without Upper Storage Areas)	•	•	-	•	
Power Windows & Remote Height Adjustment	•	•	•	•	
Rear Window	-	-	•	-	
Less Rear Window	•	•	0	•	
Bed Side Remote Control System	•	ě	-	•	
Interior Lighting with Reading and Night Light Functions	•	•	-	•	
Multi-Function Remote Control Key, 2 pieces	•	•	•	•	

Standard and Optional Features	3233S	3245S	3545		
Exterior	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	
Heated and Electrically Controlled Side Mirrors	•	•	•	•	
Spoiler & Side Extender	0	0	-	-	
250L Steel Fuel Tank (Left Side)	0	0	-	-	
5900 mm Wheelbase	0	0	-	-	
8 Ton Front Axle Capacity	0	0	•	•	
HVO Compatability	-	•	•	•	
Engine PTO	0	0	0	0	
Twin PTO (Low and High Ratio)	0	0	0	0	
Flange Type Direct Output PTO	0	0	0	0	
Pump Type Direct Output PTO	0	0	0	0	
Flange Type Offset Output PTO	0	0	0	0	
Pump Type Offset Output PTO	0	0	0	0	
Hydraulic Cab Tilting	•	•	•	•	
Electrically Operated Cab Tilting	0	0	0	0	
FL, EX/II & AT Classification ADR Package	0	0	0	0	
Without Front Spare Tire	0	0	0	0	
Front Spare Tire / Rim	•	•	•	•	
LED Headlamps	0	0	0	0	
Halogen Headlamps	•	•	•	•	
Residual Pack	0	0	-	-	
Rain Sensor & Autolamps	0	0	-	-	
Adaptive Cruise Control (ACC)	-	0	-	-	
AGM Battery	0	0	0	0	
EFB (240 Ah) Battery	•	•	•	•	
Full Trailer - O3 (up to 10T towing capability)	-	-	0	0	
Full Trailer - O4 (more than 10T towing capability)	-	-	0	0	
Construction Capacity Increase Package (9 ton front axle, 385/65 R 22,5 front tires, Electro-Hydraulic Steering Wheel -EHPAS, 22.5X11.75 Steel)	-	-	0	0	
Switchable Air Brake Compressor	-	•	•	•	
Smart Tachograph	•	•	•	•	
Short Bumper	-	-	•	•	
Medium Bumper	•	•	-	-	
Cold Pack	0	0	0	0	
Front Towing Hooks	0	0	•	•	
Beacon Lamp	-	-	0	-	
Double Roof Beacon Lamp (Passenger Side Lamp & Driver Side Infrastructure)	-	-	0	0	

[•] Standard o Optional

Technical Measurements

August 2025



Dimensions (mm)	3233S	3245S	35	45
Dillielisions (IIIII)	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab
Wheelbase (B&C)	5200	5200	4500	4500
Overall Length (G)	9887	9885	9165	9165
Front Overhang (A)	1450	1450	1450	1450
Rear Overhang (F)	1924	1919	1750	1750
Distance Between 1st and 2nd Wheel Centers (B)	3773	3780	4500	4500
Distance Between 2nd and 3th Wheel Centers (C)	1421	1408	1350	1350
Distance Between 3th and 4th Wheel Centers (E)	1319	1328	-	-
Overall Vehicle Width (Excluding Mirrors) (J)	2540	2540	2540	2540
Overall Cab Length (I)	2260	2260	1777	2260
Total Vehicle Height (H)	3390	3390	3140	3140
Turning Radius	-	-	10730	10730
Useful Chassis Length	7108	7108	6695	6465

	Weights (kg)	1st Axle	2nd Axle	3rd Axle	4th Axle	Total
	Technically Permissible Weight	7500	7500	12000	8700	33000
3233S	Kerb Weight	5309	1440	1925	1311	9985
(High Roof Sleeper Cab)	Payload	2191	6060	10075	7389	23015
	Regulatory Permissible Weight	7500	7500	9500	8700 1311	32000
	Technically Permissible Weight	7500	7500	12600	2000 8700 1925 1311 0075 7389 9500 8500 2600 10400 1925 1311 0675 9089 9500 8500 3400 - 2243 - 3400 - 3400 - 2243 - 1157 - 1157 -	33000
3245S (High Roof Sleeper Cab)	Kerb Weight	5587	1607	1925	1311	10430
	Payload	1913	5893	10675	9089	22570
	Regulatory Permissible Weight 7500 7500 Technically Permissible Weight 8000 13400	7500	9500	8500	32000	
	Technically Permissible Weight	8000	13400	13400	-	34000
3545	Kerb Weight	5301	2691	2243	-	10235
(Day Cab)	Payload	2699	10709	11157	8700 1311 7389 8500 10400 1311 9089 8500	23765
	Regulatory Permissible Weight	8000	9500	9500		26000
	Technically Permissible Weight	8000	13400	13400	1311 7389 8500 10400 1311 9089 8500	34000
3545	Kerb Weight	5438	2691	2243	-	10372
(Low Roof Sleeper Cab)	Payload	2562	10709	11157	1311 7389 8500 10400 1311 9089 8500	23628
	Regulatory Permissible Weight	8000	9500	9500	-	26000

^{*}The kerb weight data includes a 90% full fuel tank, other fluids, tools, a spare tire, and a driver weighing 75 kg. Weight values may vary depending on the vehicle configuration.

