



Technical Features

F-LINE Tractor Series





*The vehicle image may differ from the actual vehicle.

Technical Features	1845T		3551T		
	Low Roof Sleeper Cab	Extra High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	High Roof Sleeper Cab
Engine					
Type	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm
Displacement (cc)	12.740 cm3	12.740 cm3	12.740 cm3	12.740 cm3	12.740 cm3
Power PS (kW)	450 PS (330 kW) @ 1800 rpm	450 PS (330 kW) @ 1800 rpm	510PS (375 kW) @1800 rpm	510PS (375 kW) @1800 rpm	510PS (375 kW) @1800 rpm
Torque	2300 Nm @ 900-1300 rpm	2300 Nm @ 900-1300 rpm	2600Nm @ 1000-1300 rpm	2600Nm @ 1000-1300 rpm	2600Nm @ 1000-1300 rpm
Powertrain					
Clutch	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc
Transmission / Ratios	Automated: Ecotorq 16S 2600 DD AMT (17,03 - 1,00)	Automated: Ecotorq 16S 2600 DD AMT (17,03 - 1,00)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)
Forward and Reverse Gear	16 forward + 4 reverse	16 forward + 4 reverse	16 forward + 2 reverse	16 forward + 2 reverse	16 forward + 2 reverse
FDR	2,64	2,64	4,87	4,87	4,87
Axle & Suspension					
Axle Configuration	4x2	4x2	6x4	6x4	6x4
Front Axle	8 T	8 T	8 T	8 T	8 T
Rear Axle	XSS - 510, 13.5 T	XSS - 510, 13.5 T	XPT - 330, 16 T	XPT - 330, 16 T	XPT - 330, 16 T
Suspension	Parabolic Front Leaf Spring/ 4 Bellow Rear Air Suspension	Parabolic Front Leaf Spring/ 4 Bellow Rear Air Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension
Brakes					
Brake System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Separator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Separator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Separator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Separator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Separator and Heater
Service Brake	Front and Rear Disc Brakes	Front and Rear Disc Brakes	Front and Rear Drum Brakes	Front and Rear Drum Brakes	Front and Rear Drum Brakes
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 - Disc Brakes	430 x 45 - Disc Brakes	410 X 200, Z-Cam Drum Brake	410 X 200, Z-Cam Drum Brake	410 X 200, Z-Cam Drum Brake
Engine Brake Power	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)
Hydraulic Retarder	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160kW	max. 450 kW / continuous 160kW	max. 450 kW / continuous 160kW
Fuel & AdBlue Tank					
Fuel Tank	600L, Right Hand Side, Aluminum	600L, Right Hand Side, Aluminum	400L, Right Hand Side, Aluminum	400L, Right Hand Side, Aluminum	400L, Right Hand Side, Aluminum
SCR Tank	78 L	78 L	55 L	55 L	55 L
Chassis					
Thickness and Material	U Profile, High Strength, 10 mm Thickness, S500 MC Material	U Profile, High Strength, 10 mm Thickness, S500 MC Material	U Profile, High Strength, 10 mm Thickness, S500 MC Material	U Profile, High Strength, 10 mm Thickness, S500 MC Material	U Profile, High Strength, 10 mm Thickness, S500 MC Material
5th Wheel					
Brand / Model / Height	SAF Holland / SK-S 36.20 / 185 mm / 1200 mm	SAF Holland / SK-S 36.20 / 185 mm / 1200 mm	JOST / JSK38MC / 190 mm / 1400 mm	JOST / JSK38MC / 190 mm / 1400 mm	JOST / JSK38MC / 190 mm / 1400 mm
Mounting Plate Height	40 mm	40 mm	40 mm	40 mm	40 mm
Tires					
Front Axle	315/70 R 22.5	315/70 R 22.5	315/80 R 22.5	315/80 R 22.5	315/80 R 22.5
Rear Axle	315/70 R 22.5	315/70 R 22.5	315/80 R 22.5	315/80 R 22.5	315/80 R 22.5
Rims	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel

Standard and Optional Features	1845T		3551T		
	Low Roof Sleeper Cab	Extra High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	High Roof Sleeper Cab
Safety & Technology					
Pre-Collision Assist	•	•	-	-	-
Lane Keeping Alert (LDWS)	•	•	•	•	•
Electronic Stability Program (ESP)	•	•	•	•	•
Driver Alert System	•	•	•	•	•
Moving-off Information System (MOIS)	•	•	•	•	•
Rear View Camera	•	•	•	•	•
Blind Spot Information System (BLIS)	•	•	•	•	•
Alcohol Interlock Facilitation	•	•	•	•	•
Traffic Sign Recognition	•	•	•	•	•
Emergency Stop Signal	•	•	•	•	•
Tire Pressure Monitoring System (TPMS)	•	•	•	•	•
Auto High Beam Headlamps	◊	◊	-	-	-
Pre-Collision Assist with Pedestrian Detection	◊	◊	-	-	-
Intelligent Adaptive Cruise Control with Stop & Go (IACC)	◊	◊	-	-	-
Electronic Brake System with ABS & ATC (EBS)	•	•	•	•	•
Retarder	◊	◊	◊	◊	◊
Adaptive Cruise Control (ACC) (only with optional tech package)	◊	◊	-	-	-
Predictive Cruise Control (PCC)	•	•	-	-	-
Electro-Hydraulic Steering System (EHPAS)	-	-	◊	◊	◊
Differential Lock	•	•	•	•	•
Interior					
Multimedia System with 9" Touch Screen (DAB Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)	•	•	•	•	•
Navigation	◊	◊	◊	◊	◊
12" Ghost Cluster	•	•	•	•	•
Driver Facing Camera	•	•	•	•	•
Improved Sound and Heat Insulation	•	•	•	•	•
Air Conditioning	•	•	•	•	•
Dry & Wet Type Cab Heater	◊	◊	-	-	-
Wet Type Cab Heater	-	-	◊	◊	◊
Dry Type Cab Heater	•	•	-	•	•
Manual Sunroof	•	-	◊	•	•
Electric Sunroof	-	•	-	-	-
Dual Passenger Seat	-	-	◊	-	-
Driver Seat Armrests	•	•	•	•	•
Heated and Air Suspension Driver Seat	•	•	•	•	•
Exterior Survivor	-	•	-	-	-
Mattress Topper for Lower Bed	◊	◊	-	◊	◊
Driver Seatbelt Warning System	•	•	•	•	•
Double Bed	-	◊	-	-	◊
Single Bed	•	•	-	•	•
Multi-Function Remote Control Key, 2 pieces	•	•	•	•	•

Standard and Optional Features	1845T		3551T		
	Low Roof Sleeper Cab	Extra High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	High Roof Sleeper Cab
Exterior					
Heated and Electrically Controlled Side Mirrors	•	•	•	•	•
Spoiler & Side Extender	-	•	-	-	◊
Side Skirt	◊	◊	-	-	-
Aluminum Rims (Ford)	◊	◊	-	-	-
Aluminum Rims (Alcoa)	◊	◊	-	-	-
Multileaf Spring Rear Mechanical Suspension	◊	◊	-	-	-
XSS - 470 Rear Axle	◊	◊	-	-	-
7.5T Front Axle Capacity	◊	◊	-	-	-
19T GVW	◊	◊	-	-	-
New Low Rolling Resistance Tires	•	•	-	-	-
450L Aluminum Fuel Tank (Left Side)	◊	◊	-	-	-
510L (Right Side) + 410L Aluminum Fuel Tank (Left Side)	◊	◊	-	-	◊
600L (Right Side) + 450L Aluminum Fuel Tank (Left Side)	◊	◊	-	-	-
No Grease 5th Wheel (1100 mm & 1200 mm)	◊	◊	-	-	-
JOST 5th Wheel	◊	◊	•	•	•
Hydraulic Cab Tilt	•	•	•	•	•
Electrically Operated Cab Tilt	◊	◊	◊	◊	◊
HVO Compatibility	•	•	•	•	•
Engine PTO (requires retarder for 1845T)	◊	◊	◊	◊	◊
NH4B Offset PTO with Flange (Double gear)	-	-	◊	◊	◊
NH4C Offset PTO without Flange (Double Gear)	◊	◊	•	•	•
Remote Transmission PTO Start-Stop Function	•	•	•	•	•
Remote Engine Stop-Start Function	•	•	•	•	•
Construction Capacity Increase Package (9 ton front axle, 385/65 R 22.5 front tires, Electro-Hydraulic Steering Wheel, EHPAS, 22.5X11.75 Steel)	-	-	◊	◊	◊
FL, EXII & AT Classification ADR Package	◊	◊	◊	◊	◊
Without Front Spare Tire	◊	◊	◊	◊	◊
Front Spare Tire / Rim	•	•	•	•	•
LED Headlamps	◊	◊	◊	◊	◊
Tail (Rear Stop) Lamp	•	•	•	•	•
Halogen Headlamps	•	•	•	•	•
Rain Sensor & Autolamps	•	•	•	•	•
AGM Battery	◊	◊	◊	◊	◊
EFB (240 Ah) Battery	•	•	•	•	•
Adjustable Air Compressor	•	•	•	•	•
Smart Tachograph	•	•	•	•	•
Cabin With Air Suspension	◊	◊	-	-	-
Black Front Grill	•	•	•	•	•
Short Bumper	-	-	•	-	-
Long Bumper	•	•	-	-	-
Body Color Bumper	•	•	•	•	•
Eco+Mode	•	•	-	-	-
Cold Pack	◊	◊	◊	◊	◊
Front Towing Hooks	◊	◊	•	•	•
Double Front Towing Hooks	◊	◊	◊	◊	◊

• Standard ◊ Optional



Dimensions (mm)	1845T			3551T	
	Low Roof Sleeper Cab	Extra High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	High Roof Sleeper Cab
Wheelbase (A)	3600	3600	3800	3800	3800
Overall Length (B)	5914	5914	7495	7495	7495
Front Overhang (C)	1450	1450	1450	1450	1450
Rear Overhang (D)	872	872	905	905	905
Distance Between 1st and 2nd Wheel Centers (A)	3592	3592	3790	3790	3790
Distance Between 2nd and 3rd Wheel Centers (H)	-	-	1350	1350	1350
Overall Vehicle Width (Excluding Mirrors) (E)	2540	2540	2540	2540	2540
Overall Cab Length (F)	2254	2254	1777	2260	2310
Total Vehicle Height (G)	3023	3943	3354	3354	3868
Turning Radius	7560	7560	9700	9700	9700
Useful Chassis Length	3394	3394	5140	4755	4755

Tire & FDR	5th Wheel Height	FDR	Rear Tire	Loaded 5th Wheel Height (10 mm Tolerance)	Unloaded 5th Wheel Height (10 mm Tolerance)
1845T	980 mm	2,31 & 2,47	295/60 R22.5	976 mm	999 mm
	1100 mm	2,47 & 2,64	315/70 R22.5	1120 mm	1147 mm
	1150 mm	2,64	295/80 R22.5	1161 mm	1194 mm
	1200 mm	2,64	295/80 R22.5	1161 mm	1225 mm
	1200 mm	2,64	315/70 R22.5	1189 mm	1213 mm
	1200 mm	2,64	315/80 R22.5	1221 mm	1245 mm
	1250 mm	2,64	315/80 R22.5	1286 mm	1310 mm
	1250 mm	2,64	295/60 R22.5	1264 mm	1290 mm
3551T	1350 mm	4,87	315/80 R22.5	-	1380 mm
	1400 mm	4,87	315/80 R22.5	-	1404 mm
	1450 mm	4,87	315/80 R22.5	-	1464 mm

Weights (kg)		1st Axle	2nd Axle	3rd Axle	Total
1845T (Low Roof Sleeper Cab)	Technically Permissible Weight	8000	12600	-	18000
	Kerb Weight	5443	2566	-	8009
	Payload	2557	10034	-	9991
	Regulatory Permissible Weight	7500	11500	-	18000
1845T (Extra High Roof Sleeper Cab)	Technically Permissible Weight	8000	12600	-	18000
	Kerb Weight	5530	2566	-	8096
	Payload	2470	10034	-	9904
	Regulatory Permissible Weight	7500	11500	-	18000
3551T (Day Cab)	Technically Permissible Weight	8000	13400	13400	32000
	Kerb Weight	5445	2860	2412	10717
	Payload	2555	10540	10988	21283
	Regulatory Permissible Weight	8000	9500	9500	25000
3551T (Low Roof Sleeper Cab)	Technically Permissible Weight	8000	13400	13400	32000
	Kerb Weight	5582	2860	2412	10854
	Payload	2418	10540	10988	21146
	Regulatory Permissible Weight	8000	9500	9500	25000
3551T (High Roof Sleeper Cab)	Technically Permissible Weight	8000	13400	13400	32000
	Kerb Weight	5629	2860	2412	10901
	Payload	2371	10540	10988	21099
	Regulatory Permissible Weight	8000	9500	9500	25000

*The kerb weight data includes a 90% full fuel tank, other fluids, tools, a spare tire, and a driver weighing 75 kg. Weight values may vary depending on the vehicle configuration.

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.

