FORD **TRUCKS** 4142D L EURO6

Basic Features					
Vehicle Type	Tipper				
Axle	8x4				
Emission	Euro 6				
Cabin Type	Day Cab				
Wheelbase (mm)	5100				
Engine					
Туре	Ecotorq 12,7 litre				
Displacement (cc)	12740				
Diameter x Stroke	130 mm x 160 mm				
Power	450 PS (353 kW) / 1800 RPM				
Torque	2500 Nm / 1100-1200 RPM				
Compression Ratio	17 +/- 0,5 : 1				
Oil Filling Volume	50 L				
Coolant Volume	57 L (77 L with Intarder)				
Transmission					
Clutch	430 mm Single Disc				
Automated Transmission / Ratios (1. gear - 16. gear)	Ecotorq 16S 2600 OD (14,107 - 0,823)				
Steering					
	Electro Hydraulic Power Assisted Steering System				
Chassis					
Chassis Thickness	10 mm with Reinforcement				
Chassis Strength	500 MPa				
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Reinforced Parabolic Suspension				
Axle	Single Reduction				
Axle Ratio	4,87 / 4,08				
Tyres	315/80 R 22,5				
Wheel Rim	22,5 x 9 Steel				
Braking System					
Brakes (Ø mm x mm Length)	430 x 45 - Disc Brakes				
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Engine Brake Power	max. 320 kW (Engine Level)				
Intarder Power	max. 450 kW / Continuous 160 kW				
Electrical System					
Battery	24V, 2 x 12V 150 Ah				
Alternator / Starter Motor	130 A / 6,5 kW				
Tanks					
Fuel Tank	315 L Aluminium				
SCR Tank	55 L				



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Total Vehicle Height			3245		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6490		
Chassis Height - Front			1185		
Chassis Height - Rear			1186		
Ground Clearance - Front			380		
Ground Clearance - Rear			296		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	7500	7500	10500	10500	36000
Kerb Weight	3527	3424	1825	1824	10600

3973

8000

STANDARD EQUIPMENT

- Manuel Air conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Transmission Offset (single gear) PTO without Flange & Interior Control Unit
- Cruise Control
- Drum Brake

Payload

GVM (Legal)

- **Engine Brake**
- **Electrically Operated Windows**
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Switchable Air Compressor for Improved Fuel Economy
- Lumbar Support
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- **Immobilizer**
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Front Towing Hooks (Double Hook)
- Short Bumper
- DAB Radio***
- Automatic Traction Control (ATC)
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Technology Pack 1 (Cybersecurity Improvements, Rear Parking Aid (RPA), Moving-off Information System (MOIS), Blind Spot Information System (BLIS), Tire Pressure Monitoring System (TPMS), Emergency Stop Signal, Alcohol Interlock Facilitation, Intelligent Speed Asistance, Driver Drowsiness Attention Warning, Lane Departure Warning System (LDWS))

OPTIONAL EQUIPMENT

- Automated Transmission (with Normal Mode, Off-Road Mode, Rocking Mode)
- Engine Driven PTO & Interior Control Unit

8675

9500

Transmission Direct (double gear) PTO without Flange

8676

9500

25400

32000

Intarder

4076

8000

- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Wet Type Cab Heater and 225 Ah Rattery*
- Power Cab Tilting
- Rear Window **
- 4750 mm Wheelbase Version
- Double Passenger Seat
- Extra Heavy Duty Pack (Available With 13R 22,5 Tyre)
- 3,5T Towing Capability
- 10T Towing Capability
- 27T Towing Capability
- Manually Operated Sunroof
- Front Vehicle Antiroll Bar
- Oil Pan Protection
- Multileaf Spring Front Suspension
- Lateral Protection
- Automatic Traction Control (ATC)
- Reinforced Wheel Rim
- **Less Spare Tire**
- Rear Towing Hook Option
- 4300 mm Wheelbase Version
- Hub Reduction
- Twin PTO (high ratio) / Twin PTO (low ratio)****
- 8 T Front Axle Capacity

* Not Available with 4750 mm Wheelbase Version. ** Not Available with Low Roof Sleeper Cab Version

*** DAB Radio can be standard or optional according to the market.

****Only available with Automated Transmission.