



Technical Features

F-LINE

Light Weight Construction Series



Sharing the load


Technical Features	3545M L	4145M L	3545D L		4145D L	
Engine	Day Cab	Day Cab	Day Cab	Low Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab
Type	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm	GEN2 Ecotorq Euro 6 130 mm x 160 mm
Displacement (cc)	12.740 cm3	12.740 cm3	12.740 cm3	12.740 cm3	12.740 cm3	12.740 cm3
Power PS (kW)	450 PS (353 kW) @ 1800 d/d	450 PS (353 kW) @ 1800 d/d	450 PS (353 kW) @ 1800 d/d	450 PS (353 kW) @ 1800 d/d	450 PS (353 kW) @ 1800 d/d	450 PS (353 kW) @ 1800 d/d
Torque	2500 Nm @ 1100-1200 d/d	2500 Nm @ 1100-1200 d/d	2500 Nm @ 1100-1200 d/d	2500 Nm @ 1100-1200 d/d	2500 Nm @ 1100-1200 d/d	2500 Nm @ 1100-1200 d/d
Powertrain						
Clutch	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc
Transmission / Ratios	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823)
Forward and Reverse Gear	16 forward + 2 reverse	16 forward + 2 reverse	16 forward + 2 reverse	16 forward + 2 reverse	16 forward + 2 reverse	16 forward + 2 reverse
FDR	4,08	4,08	4,08	4,08	4,87	4,87
Axle & Suspension						
Axle Configuration	6x4	8x4	6x4	6x4	8x4	8x4
Front Axle	8 T	8 T	8 T	8 T	8 T	8 T
Rear Axle	XST - 420, 11 T	XST - 420, 11 T	XST - 420, 11 T	XST - 420, 11 T	XST - 420, 11 T	XST - 420, 11 T
Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension	Parabolic Front Leaf Spring/ Mechanical Rear Suspension
Brakes						
Brake System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater
Service Brake	Front and Rear Disc Brake	Front and Rear Disc Brake	Front and Rear Disc Brake	Front and Rear Disc Brake	Front and Rear Disc Brake	Front and Rear Disc Brake
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 Disc Brake	430 x 45 Disc Brake	430 x 45 Disc Brake	430 x 45 Disc Brake	430 x 45 Disc Brake	430 x 45 Disc Brake
Engine Brake Power	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)
Hydraulic Retarder	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW
Fuel & AdBlue Tank						
Fuel Tank	315L, Right Hand Side, Aluminium	315L, Right Hand Side, Aluminium	315L, Right Hand Side, Aluminium	315L, Right Hand Side, Aluminium	315L, Right Hand Side, Aluminium	315L, Right Hand Side, Aluminium
SCR Tank	55 L	55 L	55 L	55 L	55 L	55 L
Chassis						
Thickness and Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material	U Profile, High Strength, 8 mm Thickness, S500 MC Material
Tires						
Front Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5
Rear Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5
Rims	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel

Standard and Optional Features	3545M L	4145M L	3545D L		4145D L	
Safety & Technology	Day Cab	Day Cab	Day Cab	Low Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab
Pre-Collision Assist	○	○	○	○	○	○
Lane Keeping Alert (LDWS)	●	●	●	●	●	●
Electronic Stability Program (ESP)	●	●	●	●	●	●
Driver Alert System	●	●	●	●	●	●
Moving-off Information System (MOIS)	●	●	●	●	●	●
Rear View Camera	●	●	●	●	●	●
Blind Spot Information System (BLIS)	●	●	●	●	●	●
Alcohol Interlock Facilitation	●	●	●	●	●	●
Traffic Sign Recognition	●	●	●	●	●	●
Emergency Stop Signal	●	●	●	●	●	●
Tire Pressure Monitoring System (TPMS)	●	●	●	●	●	●
Auto High Beam Headlamps	○	○	○	○	○	○
Pre-Collision Assist with Pedestrian Detection	○	○	○	○	○	○
Electronic Brake System with ABS & ATC (EBS)	●	●	●	●	●	●
Electro-Hydraulic Steering System (EHPAS)	-	●	-	-	●	●
Retarder	-	○	○	○	○	○
Differential Lock	●	●	●	●	●	●
Interior						
Multimedia System with 9" Touch Screen (DAB Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)	●	●	●	●	●	●
Navigation	○	○	○	○	○	○
Improved Sound and Heat Insulation	●	●	●	●	●	●
Manual Sunroof	○	○	○	●	○	●
Air Conditioning	●	●	●	●	●	●
Dry Cab Heater	-	-	-	○	-	-
Dry & Wet Type Cab Heater	-	-	-	○	-	-
Wet Type Cab Heater	○	○	-	○	○	-
Dual Passenger Seat	○	○	○	-	○	-
Driver Seat Armrest	○	○	○	●	○	●
Adjustable Steering Wheel	●	●	●	●	●	●
Driver Seatbelt Warning System	●	●	●	●	●	●
Mattress Topper for Lower Bed	-	-	-	○	-	○
Single Bed (Without Upper Storage Ares)	-	-	-	●	-	●
Improved Sound and Heat Insulation in the Cabin	●	●	●	●	●	●
Bed Side Control System	●	●	●	●	●	●
Interior Lighting with Reading and Night Light Functions	●	●	●	●	●	●
Multi-Function Remote Control Key, 2 pieces	●	●	●	●	●	●


Standard and Optional Features	3545M L	4145M L	3545D L		4145D L	
Exterior	Day Cab	Day Cab	Day Cab	Low Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab
Full Trailer - O4 (more than 10T towing capability)	-	-	o	o	o	o
4,08 FDR	●	●	●	●	o	o
4,11 FDR	o	o	o	o	o	o
4,87 FDR	-	-	o	o	●	●
Composite Leaf Spring Rear Suspension	o	o	o	o	o	o
XPT-330 Rear Axle	o	o	o	o	o	o
385/65 R22.5 Front Tire (With 315/80 R 22.5 Rear Tire)	-	o	-	-	o	o
315L Aluminum Fuel Tank (Right Side)	●	●	●	●	●	●
300L Aluminum Fuel Tank (Right Side)	-	o	o	o	o	o
250L Aluminum Fuel Tank (Right Side)	-	o	-	-	o	o
3300 mm Wheelbase	-	-	o	o	-	-
3800 mm Wheelbase	●	-	●	●	-	-
4400 mm Wheelbase	-	o	-	-	o	o
4750 mm Wheelbase	-	-	-	-	o	o
5100 mm Wheelbase	-	●	-	-	●	●
HVO Compatability	●	●	●	●	●	●
Engine PTO	●	●	o	o	o	o
Pump Type Offset Output PTO	o	o	●	●	●	●
Pump Type Direct Output PTO	o	o	-	-	o	o
Flange Type Offset Output PTO	o	o	o	o	o	o
Flange Type Direct Output PTO	o	o	o	o	o	o
Twin PTO (Low and High Ratio)	o	o	o	o	o	o
Hydraulic Cab Tilting	●	●	●	●	●	●
Electrically Operated Cab Tilting	o	o	o	o	o	o
FL, EX/II, OX & AT Classification ADR Package	o	-	o	o	-	-
Aluminum Rims Except for Baloon Tyres (Alcoa)	o	o	o	o	o	o
Reinforced Wheel Rim	-	-	-	-	o	o
Without Front Spare Tire	o	o	o	o	o	o
Front Spare Tire / Rim	●	●	●	●	●	●
Horizontal Exhaust	●	●	●	●	●	●
Vertical Exhaust	-	-	o	-	-	-
LED Headlamps	o	o	o	o	o	o
Halogen Headlamps	●	●	●	●	●	●
Rain Sensor & Autolamps	o	o	o	o	o	o
225 aH Battery	●	●	●	●	●	●
Switchable Air Brake Compressor	●	●	●	●	●	●
Smart Tachograph	●	●	●	●	●	●
Air Cab Suspension	●	●	●	●	●	●
Short Bumper	●	●	●	●	●	●
Snow Plower Short Bumper	-	-	o	o	o	o
Medium Bumper	-	-	o	-	-	-
Cold Pack	o	o	o	o	o	o
Beacon Lamp	-	-	o	-	o	-
Double Roof Beacon Lamp (Passenger Side Lamp & Driver Side Infrastructure)	o	o	o	o	o	o
Front Towing Hooks	●	●	●	●	●	●

● Standard
 o Optional

3545M L & 3545D L DC



4145M L & 4145D L DC



Dimensions (mm)	3545M L	4145M L	3545D L		4145D L	
	Day Cab	Day Cab	Day Cab	Low Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab
Wheelbase (B)	3800	5100	3800	3800	5100	5100
Overall Length (G)	8260	8870	7511	7511	8850	8850
Front Overhang (A)	1450	1450	1450	1450	1450	1450
Rear Overhang (F)	1660	970	911	911	950	950
Distance Between 1st and 2nd Wheel Centers (C)	3800	2050	3800	3800	2050	2050
Distance Between 2nd and 3rd Wheel Centers (D)	1350	3050	1350	1350	3050	3050
Distance Between 3rd and 4th Wheel Centers (E)	-	1350	-	-	1350	1350
Overall Vehicle Width (Excluding Mirrors) (J)	2540	2540	2540	2540	2540	2540
Overall Cab Length (I)	2163	2150	2163	2508	2150	2510
Total Vehicle Height (H)	3081	3199	3200	3200	3200	3200

	Weights (kg)	1st Axle	2nd Axle	3rd Axle	4rd Axle	Total
3545M L (Day Cab)	Technically Permissible Weight	8000	11500	11500	-	29000
	Kerb Weight	5253	2299	2107	-	9659
	Payload	2747	9201	9393	-	19341
	Regulatory Permissible Weight	8000	9500	9500	-	26000
4145M L (Day Cab)	Technically Permissible Weight	8000	8000	11500	11500	37000
	Kerb Weight	3732	3657	1567	1372	10328
	Payload	4268	4343	9933	10128	26672
	Regulatory Permissible Weight	8000	8000	9500	9500	28000
3545D L (Day Cab)	Technically Permissible Weight	8000	11500	11500	-	29000
	Kerb Weight	5057	2146	2092	-	9295
	Payload	2943	9354	9408	-	19705
	Regulatory Permissible Weight	8000	9500	9500	-	26000
3545D L (Low Roof Sleeper Cab)	Technically Permissible Weight	8000	11500	11500	-	29000
	Kerb Weight	5156	2151	2097	-	9404
	Payload	2844	9349	9403	-	19596
	Regulatory Permissible Weight	8000	9500	9500	-	26000
4145D L (Day Cab)	Technically Permissible Weight	8000	8000	11500	11500	37000
	Kerb Weight	3816	3670	1859	1623	10385
	Payload	4184	4330	9641	9877	26615
	Regulatory Permissible Weight	8000	8000	9500	9500	28000
4145D L (Low Roof Sleeper Cab)	Technically Permissible Weight	8000	8000	11500	11500	37000
	Kerb Weight	3925	3670	1859	1623	11077
	Payload	4075	4330	9641	9877	25923
	Regulatory Permissible Weight	8000	8000	9500	9500	28000

*The kerb weight data includes a 90% full fuel tank, other fluids, tools, a spare tire, and a driver weighing 75 kg. Weight values may vary depending on the vehicle configuration.

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.

